

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: OB.003 ACTIVATOR FOR EPOXY HS
- · Article number: OB.003
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. use as industrial paint
- · Sector of Use SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Générale de Peinture, 36 rue Scheffer 75116 PARIS, France info@generalpaint.biz
- · Further information obtainable from: Product Safety Department
- · 1.4 Emergency telephone number:
- +961 9 925 990/1/2

Phone:

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008) with its amendment Regulation (EU) 2020/878



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)



Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 1)

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Isophorone Diisocyanate homopolymer Homopolymer of hexamethylene diisocyanate n-butyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eve irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

GB



Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32		>25-≤50%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	>10- <i>≤</i> 25%
CAS: 78-83-1 EINECS: 201-148-0	butanol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335-H336	>10- <i>≤</i> 25%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butan-1-ol ♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	>2.5- <i>≤</i> 10%
CAS: 90-72-2 EINECS: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol October Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	>2.5- <i>≤</i> 10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol	≤2.5%
CAS: 94266-48-5 EC number: 304-455-9	Pine oil The Flam. Liq. 3, H226; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<i>≤</i> 2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.

(Contd. on page 4)



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)



Page 5/12

Safety data sheet according to 1907/2006/EC. Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 4)

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

ECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

78-83-1 butanol

WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)



Page 6/12

(Contd. of page 5)

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: Transparent
Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 108 °C

· Flash point: 24 °C

(Contd. on page 7)



Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

	(Contd. of page
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	340 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Explosion limits: Lower: Upper:	1.1 Vol % 13 Vol %
Vapour pressure at 20 °C: Vapour pressure at 50 °C:	12 hPa 0.7 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	0.94 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: VOC (EC)	77.8 % 731.3 g/l
Solids content:	11.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 8)



Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 7)

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1,230 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 9)



Page 9/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 8)

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	
· 14.3 Transport hazard class(es)	NOT APPLICABLE	
· Class	3 Flammable liquids.	
· Laber · 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Flammable liquids. 30	

Contd. on page 10



Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

	(Contd. of page
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to An Marpol and the IBC Code	nex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n 3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 n
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 11)



Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 10)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: N/A

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

(Contd. on page 12)



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31) with its amendment Regulation (EU) 2020/878

Printing date 30.11.2023 Version number 1.0 Revision: 11.10.2023

Trade name: OB.003 ACTIVATOR FOR EPOXY HS

(Contd. of page 11)

Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.